## **AMENDMENTS TO THE CLAIMS**

1. (Currently Amended) An optical alignment apparatus using visible light source and images, comprising:

a first light source for providing light of a visible wavelength range to perform optical alignment;

a second light source providing light of an infrared wavelength range; a micrometer stage for aligning the light outputted from the first light source or the second light source with an active area of a detector;

a lensed fiber connected to the micrometer stage, for inputting light into the active area of the detector;

an optical alignment confirming means for visually confirming whether the light outputted from the lensed fiber is aligned with the active area of the detector;

an image information acquiring means connected to the optical alignment confirming means, for acquiring image information; and

a control means for operating the micrometer stage based on the image information acquired by the image information acquiring means to perform optical alignment;

an optical coupler for connecting the first light source and the second light source simultaneously and outputting input light to the first output port and the second output port of the optical coupler in a predetermined proportion; and

an optical intensity supervising means for controlling optical intensity of light inputted to the active area of the detector by being connected with the optical coupler's output port which is not connected with the detector,

wherein the control means includes the micrometer stage to compensate a difference in distances to a beam waist, the difference being generated by different wavelengths of the first light source and the second light source.

- 2. (Cancelled)
- 3. (Currently Amended) The optical alignment apparatus as recited in claim 2 1, wherein the optical coupler includes a first input port, a second input port, a first output port and a second output port.
- 4. (Original) The optical alignment apparatus as recited in claim 1, wherein the detector performs optical alignment with the light outputted from the first light source or the second light source.
  - 5. (Cancelled)
  - 6. (Cancelled)